

PATENT CLAIMS

1. Burr-examination sensor device for the examination of burrs on a workpiece, comprising at least one distance sensor (28) with a detector head (30), wherein the detector head (30) is positionable at a distance to the workpiece and detector head (30) and workpiece are movable relative to one another and wherein the detector head (30) is couplable electromagnetically to the workpiece or the workpiece is adapted to be acted upon by it with an electromagnetic signal and the coupling to the workpiece or an electromagnetic reaction signal of the workpiece to the impinging signal are dependent on a distance between detector head (30) and workpiece so that this distance is determinable without any contact and a workpiece surface is adapted to be scanned by the detector head (30) without any contact.
2. Sensor device for burr examination as defined in claim 1, characterized in that the detector head (30) has an active surface (32), a local coupling to the workpiece taking place via said surface or impinging signals being transmitted locally to workpiece surface areas and reaction signals being received from these areas via said surface.
3. Sensor device for burr examination as defined in claim 1 or 2, characterized in that detector head (30) and workpiece are movable relative to one another parallel to a distance direction.

4. Sensor device for burr examination as defined in any one of the preceding claims, characterized in that detector head (30) and workpiece are movable relative to one another transversely to a vertical distance direction.
5. Sensor device for burr examination as defined in any one of the preceding claims, characterized by a positioning device for the positioning and movement of the detector head (30) relative to the workpiece.
6. Sensor device for burr examination as defined in claim 5, characterized in that the detector head (30) is positionable by the positioning device along linearly independent coordinate directions.
7. Sensor device for burr examination as defined in claim 5 or 6, characterized in that the detector head (30) is rotatable relative to the workpiece.
8. Sensor device for burr examination as defined in any one of claims 5 to 7, characterized in that a positioning device for a tool for the machining of the workpiece is used as a positioning device for a distance sensor (28).
9. Sensor device for burr examination as defined in any one of the preceding claims, characterized in that the detector head is designed as a probe (110) or arranged in a probe.
10. Sensor device for burr examination as defined in claim 9, characterized in that the probe (110) is insertable into a bore in the workpiece.

11. Sensor device for burr examination as defined in claim 9 or 10, characterized in that electronic components of the device are arranged entirely or partially in the probe (110).
12. Sensor device for burr examination as defined in any one of the preceding claims, characterized in that a visual range of the distance sensor (28) is adjusted.
13. Sensor device for burr examination as defined in claim 12, characterized in that a visual range of the distance sensor (28) is adjustable electromagnetically.
14. Sensor device for burr examination as defined in claim 12 or 13, characterized in that the distance sensor is designed and/or screened in such a manner that the electromagnetic coupling between detector head (30) and workpiece is restricted to a specific visual range.
15. Sensor device for burr examination as defined in any one of claims 12 to 14, characterized in that the specific visual range comprises a viewing direction essentially transverse to a longitudinal direction (54) of a distance sensor (28).
16. Sensor device for burr examination as defined in any one of claims 12 to 15, characterized in that the specific visual range comprises a viewing direction essentially parallel to a longitudinal direction (54) of a distance sensor (28).
17. Sensor device for burr examination as defined in any one of the preceding claims, characterized in that a preliminary signal processing takes place in a measuring head and an evaluation unit for the burr

examination is provided.

18. Sensor device for burr examination as defined in claim 17, characterized in that an evaluation algorithm compares a measurement signal with a reference curve.
19. Sensor device for burr examination as defined in any one of the preceding claims, characterized in that the detector head (30) is provided with contacts so that it is connectable to a device arranged at a distance.
20. Sensor device for burr examination as defined in any one of claims 1 to 18, characterized in that the detector head (30) is designed as a remote unit coupleable cordlessly to a device arranged at a distance.
21. Sensor device for burr examination as defined in any one of the preceding claims, characterized in that a distance sensor is an inductive sensor (28), the detector head (30) being coupled inductively to a metallic workpiece with said sensor.
22. Sensor device for burr examination as defined in claim 21, characterized in that the distance sensor (28) has a metallic outer surface area acted upon with a voltage.
23. Sensor device for burr examination as defined in any one of claims 1 to 20, characterized in that a distance sensor is an optical distance sensor (66), the detector head acting upon the workpiece with an optical signal and registering a reflection signal with said distance sensor.
24. Sensor device for burr examination as defined in claim 23, characterized in that a light signal is coupled in and/or coupled out in a fiber optic

manner.

25. Sensor device for burr examination as defined in any one of claims 1 to 20, characterized in that a distance sensor is an ortho-inductive distance sensor, the detector head being coupled inductively to a metallic workpiece and the workpiece being acted upon by the detector head with an optical signal and a reflection signal being registerable by the detector head with said distance sensor.
26. Sensor device for burr examination as defined in any one of claims 1 to 20, characterized in that a distance sensor is a capacitive distance sensor, the detector head being coupled capacitively to the workpiece with said distance sensor.
27. Sensor device for burr examination as defined in any one of claims 1 to 20, characterized in that the distance sensor is a coupled inductive-capacitive distance sensor, an element couplable to the workpiece not only inductively but also capacitively being provided with said distance sensor.
28. Sensor device for burr examination as defined in any one of the preceding claims, characterized in that a plurality of distance sensors (66, 74) is provided.
29. Sensor device for burr examination as defined in claim 28, characterized in that sensor signals of different distance sensors are linked to one another.

30. Sensor device for burr examination as defined in claim 28 or 29, characterized in that a difference signal of distance sensors is evaluated.
31. Sensor device for burr examination as defined in any one of claims 28 to 30, characterized in that a cumulative signal of distance sensors is evaluated.
32. Sensor device for burr examination as defined in any one of claims 28 to 31, characterized in that distance sensors of the sensor device for burr examination have the same viewing direction.
33. Sensor device for burr examination as defined in any one of claims 28 to 31, characterized in that distance sensors of the sensor device for burr examination have different viewing directions.
34. Sensor device for burr examination as defined in claim 33, characterized in that distance sensors of the sensor device for burr examination have viewing directions in opposite directions.
35. Sensor device for burr examination as defined in any one of claims 28 to 34, characterized in that the distance sensors (66, 74) are fixed in position relative to one another.
36. Sensor device for burr examination as defined in any one of claims 28 to 35, characterized in that the relative position of the distance sensors (66, 74) of the sensor device for burr examination is adjustable.
37. Sensor device for burr examination as defined in any one of claims 28 to 36, characterized in that distance sensors have the same viewing plane.

45. Use of a distance sensor as defined in claim 44, characterized in that the distance sensor is coupled to the workpiece electromagnetically.
46. Use of a distance sensor as defined in claim 44 or 45, characterized in that the distance sensor is coupled to the workpiece capacitively.
47. Use of a distance sensor as defined in any one of claims 44 to 46, characterized in that the distance sensor is coupled to the workpiece inductively.
48. Use of a distance sensor as defined in claim 44, characterized in that the distance sensor comprises a detector head with a light transmitter and light receiver, wherein the workpiece is adapted to be scanned locally and optically by means of the detector head.
49. Use of a distance sensor as defined in any one of claims 44 to 48, characterized in that a local sensor field is adapted to be formed between the distance sensor and the workpiece, a distance between distance sensor and workpiece being determinable via said field.